

- 1. WHEN CUL-DE-SACS ARE LESS THAN 200' TO END OF BULB (SHORT CUL-DE-SAC), STREET SECTION SHALL BE AS SHOWN. WHEN CUL-DE-SAC IS 200' OR LONGER, THE STREET SECTION SHALL BE 34' WIDE BETWEEN FACE OF CURBS AND LOCATED WITHIN A 60' RIGHT-OF-WAY (R/W). CUL-DE-SAC BULB RADIUS AND RIGHT-OF-WAY SHOWN IS FOR LOCAL RESIDENTIAL STREETS ONLY. ALL OTHER STREET CLASSIFICATIONS SHALL BE 45' MINIMUM BULB RADIUS WITHIN A 60' RIGHT-OF-WAY.
- 2. "NO PARKING BEYOND THIS POINT" SIGNS SHALL BE INSTALLED AT BOTH SIDES OF CUL-DE-SAC BULB ENTRANCE AS SHOWN.
- 3. A 2% MIN CROSS SLOPE IS REQUIRED FROM CENTER OF BULB TO GUTTER. MINIMUM GUTTER SLOPE SHALL BE 0.5%.
- 4. MAINTAIN NORMAL CROWN LINE TO CENTER OF CUL-DE-SAC BULB. OFFSET FROM STREET CENTERLINE TO CENTER OF BULB EQUALS THE BULB RADIUS MINUS ONE-HALF THE STREET WIDTH.

